

Estop Hydrocell

Cross Linked, Non-Absorbent, Closed Cell, Polyethylene Joint Filler

Description

Estop Hydrocell is a cross linked, semi-rigid, closed cell polyethylene sheet material used for forming or filling expansion joints between adjacent in-situ and precast components. **Estop Hydrocell** provides excellent support backing to elastomeric sealants and is especially recommended for use in expansion joints in brickwork and in the construction of water retaining and excluding structures.

Estop Hydrocell has been tested by SIRIM in accordance to ISO 845:2006 for Apparent Density and complied with the specification in this data sheet.

Uses

Estop Hydrocell is a particularly recommended for water retaining or excluding structure.

- Potable water reservoirs
- Culverts and canals
- Sewage tanks
- Roadways and hardstandings
- Retaining walls
- Basement structures and subways
- Runways, taxiways and aprons

Advantages

- Cross linked to resist lateral and hydrostatic pressure
- High density support of sealant to prevent adhesion failure
- Non-absorbent closed cell structure
- High recovery under compression
- Non-extruding
- Low load transfer to joint edges
- Non-tainting and rot proof
- Chemically resistant
- Bitumen free
- Natural bond breaker

Standards Compliance

- **ISO 845:2006**
- **MS 1583: Part 1&2**
- **ISO 1798**
- **ISO 8067**
- **ISO 1856**

Physical Properties

Composition	Polyethylene (PE)
Appearance/Colour	Black
Density, kg/m ³ ISO 845:2006	80±10%
Potable Condition MS 1583: Part 1&2	Complied
Tensile Strength, MPa ISO 1798	>0.75
Elongation at Break, % ISO 1798	>88
Tear Strength, N/cm ISO 8067	>8
Compression Set, % @ 23°C (Change in Thickness) ISO 1856	>15

Application Instructions

Joint Sealing Slots

When forming expansion joints with **Estop Hydrocell** in in-situ concrete, joint sealing slots can be readily formed in the following manner.

Before installing, simply cut off a strip to the required depth. Pin the strip back by using 50 mm nails at approximately 100 mm intervals. Then install the filler flush with the finished surface.

Prior to sealing, the top strip can then be pulled easily from the joint to provide an uncontaminated sealing slot ready for preparation and sealing.

As elastomeric sealants will not bond to **Estop Hydrocell** the additional need for bond breaker strips is eliminated.

Packaging & Size

Estop Hydrocell is supplied in the following sheet sizes and can be easily cut to the required size with Stanley knife or saw.

10mm x 2m x 1m (20 sheets / bundle)

12mm x 2m x 1m (20 sheets / bundle)

20mm x 2m x 1m (10 sheets / bundle)

25mm x 2m x 1m (10 sheets / bundle)

(Other thickness is available upon request)

231007

Technical Support

Denka offers a technical support package to specifiers, end-users and contractors, as well as on-site technical assistance.

Storage

Estop Hydrocell should be stored in a clean area and should not be left exposed to direct sunlight for long periods, especially in hot climates.

Precaution

There are no known health hazards associated with **Estop Hydrocell** in normal use.

Additional Information

Denka Construction Solutions Malaysia Sdn Bhd offers a wide range of complementary products, which includes waterstops, waterproofing products, grouts, anchors, specialized flooring products. In addition, a wide range of products formulated for repair and refurbishment of spalled concrete are available.



Denka Construction Solutions Malaysia Sdn Bhd
(591858-U)

No. 18, Jalan Utas 15/7, Seksyen 15,
40200 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel: +603 5510 8810 Fax: +603 5518 8202

www.denka-cs.com

Limitation of Liability

The information contained in this brochure provides general advice for potential customers for DENKA about the basic properties and characteristics of various DENKA products (hereafter known as "the Product Information"). DENKA makes no warranty or representation as to the entire accuracy or completeness of the Product Information in the brochure. Nothing in this brochure will be deemed to create any express or implied warranty of merchantability, fitness for a particular purpose or infringement of any intellectual property rights. Each user of the Product Information and DENKA products assumes their own responsibility to properly determine the manner and suitability of use of the Product Information and DENKA products in its own operations. The user should exercise proper care in considering the Material Safety Data Sheet, Product Information and any other technical information provided by DENKA including descriptions of the conditions of use, warnings and other cautionary instructions. DENKA reserves the right to change the Product Information from time to time at its discretion and without notice.